ase type a plus sign (+) inside this box -> +

PTO/SB/05 (1/98)

sype a plus sign (+) inside this box

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION **TRANSMITTAL**

Attorney Docket No. 462-99-012 First Inventor or Application Identifier GILBERT AIRCRAFT CABIN PERSONAL TELEPHONE MICROCELL

Only for new non	provisional applications under 37	UFR 1.53(b))	Express M	ail Label No.	EL4473280900	<u> </u>	
	PPLICATION ELEMENTS ter 600 concerning utility patent a	pplication contents.		ADDRESS	TO: Box Pate	nt Commiss ent Applicat aton, DC 20	
1. X Plea credit pende credit pende credit pende credit pende core core core core core core core cor	ase charge the fees indicated on the toverpayments or charge any and lency of this application to Deposit edification ferred arrangement set forth below asscriptive title of the Invention cass References to Related Apatement Regarding Fed spone ackground of the Invention rief Summary of the Invention rief Summary of the Invention rief Description of the Drawing etailed Description laim(s) construct of the Disclosure awing(s) (35 U.S.C. 113) Copy from a prior application of the Invention rief Description laim(s) Copy from a prior application of the Invention rief Description laim(s) DELETION OF IN	ne attached fee trans all fees due through Account No. 01-112 fotal Pages] pplications sored R & D dix sotal Sheets] for copy) ation (37 C.F.R. § fish Box 17 complete for sored to the prior application, from weight and the sure of the account attended to the sure of the account attended by reference account attached deleting the sure of the account attended to the account attached deleting the sure of the sure of the account attached deleting the sure of the s	to the 25. 1.63(d)) ing cation, 33(b). ed) which a cop, is appanying therein.	7. Nucleotide (if applicab a. b. c. ACCOM 8. Assig 9. 37 C. (whee 10. Engli 11. Inform 11. State 12. Prelim 13. X Retun (Shoot 14. Shoot 15. Certii (if for y 16. X Othe * A new statement one has been filed the requisite informat of prior a	and/or Amino A le, all necessary Computer R Paper Copy Statement v PANYING API Inment Papers (in F.R.§3.73(b) Statement Panying Amendment (IDS)/PTO minary Amendment Receipt Postor all Entity ment(s) SB/09-12) fied Copy of Priority is circums of the priority of the priority is circums of the priority of the priority is circums of the priority of the priority is circums of the priority of the prior	Program (Acid Sequency) Readable Coverifying identical everifying identi	Appendix) nce Submission copy to computer copy entity of above copies ON PARTS et & document(s)) Power of Attorney if applicable) Copies of IDS Citations Citations Copies of IDS Copies of IDS Citations Copies of IDS Copies of IDS Citations Copies of IDS Citations Copies of IDS Copies of
		18. CORRESI	PONDENC	E ADDRESS			
☑ Custome	er Number or Bar Code Label	(Insert Customer N	00012 lo. or Attach	.8 bar code label here)	or 🗆	Correspon	dence address below
Name	Eric G. Halsne Honeywell International Inc						
Address	101 Columbia Road, P. O. I	Box 2245					
City	Morristown		State	NJ	Zip Cod	ie o	7962
Country	USA	Teleph	one	(425) 376-2107			125) 885-8797
Name (Pi					No. (Attorney/Agent)		46,753
Signature	260	alue				Date 9	1/19/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Complete if Known Unknown

property (times number of properties)

Filing a submission after final rejection (37 CFR 1.129(a))

SUBTOTAL (3)

(\$)

0.00

For each additional invention to be examined (37 CFR 1.129(b))

M ū 1

Code (\$)

104 260

103 18

102 78

109 78

110 18 Code (\$)

Claims in excess of 20

Independent claims in excess of 3

** Reissue independent claims over original patent

** Reissue daims in excess of 20 and over original patent

(\$)

924.00

Multiple dependent claim, if not paid

203 9

202 39

204 130

209 39

210 9

SUBTOTAL (2)

PTC/SB/17 (2/98)
Approved for use through 9/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Application Number

LEEE TOAKICKHITTA	4	Appli	catio	n Nun	nber	Unknown	
FEE TRANSMITTA	L	Filing	Date	3		September 18, 2000	
Patent fees are subject to annual revision on October 1. These are the fees effective October 1, 1997.		First	Nam	ed Inv	entor	David Gilbert	
Small Entity payments <u>must</u> be supported by a small entity state otherwise large entity fees must be paid. See Forms PTO/SB/t		Exan	niner	Name)	N/A	
See 37 C.F.R. §§ 1 27 and 1.28.		Grou	p/A	rt Unit		N/A	
TOTAL AMOUNT OF PAYMENT (\$) 1,614.00		Attor	ney [Docke	l No.	462-99-012	
METHOD OF PAYMENT (check one)	Π			F	EE CA	ALCULATION (continued)	
The Commissioner is hereby authorized to charge indicated fees and credit any over payments to: Deposit O1-1125	Lar Fee		Sma Fee		ty	Fee Description	Fee Paid
Number Deposit Account Honeywell International Inc.	127		227	25	Surcha	arge - late provisional filing fee or	
Charge Any Additional Fee Required Under 37 C F R. §§ 1 16 and 1 17 of the Notice of Allowance	139 141 111	7 2,520	147	130 2,520 920*	For fili	sneet. nglish specification ng a request for reexamination esting publication of SIR prior to	
2. Payment Enclosed: Check Order Other		3 1,840*	113		Exami Reque Exami	ner action esting publication of SIR after ner action sion for reply within first month	
FEE CALCULATION	110		215	190		sion for reply within second month	<u> </u>
1. BASIC FILING FEE	111			435	Exten	sion for reply within third month	
Large Entity Small Entity Fee Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$)	1	8 1,360 8 1,850				sion for reply within fourth month sion for reply within fifth month	
101 690 201 345 Utility filing fee 690.00	111	9 300	219	150	Notice	of Appeal	
106 310 206 155 Design filing fee	12	300	220	150	Filing	a brief in support of an appeal	
107 480 207 240 Plant filing fee	12	1 260	221	130	Reque	est for oral hearing	<u> </u>
108 690 208 345 Reissue filing fee	13	8 1,510	138	1,510		n to institute a public use proceeding	
114 150 214 75 Provisional filing fee	14	0 110	240	55		n to revive - unavoidable	
SUBTOTAL (1) (\$) 690.00	14	1 1,210	241	605		n to revive - unintentional	
2. EXTRA CLAIM FEES Fee from	1	2 1,210			-	issue fee (or reissue)	
Extra Claims below Fee Paid	3 8			215	_	n issue fee	
Total Claims 41 -20** = 21 X 18 = 378	14			290		issue fee	
Independent 10 - 3** = 7 X 78 = 546 Multiple Dependent	12			130		ons to the Commissioner	
· · · · · · · · · · · · · · · · · · ·	12		123	50		ons related to provisional applications	
**or number previously paid, if greater; For Reissues, see below Large Entity Small Entity	/ 12 58		581	240 40		ission of Information Disclosure Stmt	

SUBMITTED B	Y				Complete (if	applicable)
Typed or Printed Name	Eric G. Halsne				Reg. Number	46,753
Signature	Er6Ma	line	Date	9/19/2000	Deposit Account User ID	01-1125

Reduced by Basic Filing Fee Paid

146 690 246 345

149 690 249 345

Other fee (specify)

Other fee (specify)

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

PATENT APPLICATION

AIRCRAFT COMMUNICATION FREQUENCY NOMINATION

Inventor(s):

David Gilbert

13220 Barkley Street Overland Park, KS 66209

A Citizen of the United Kingdom

Assignee:

Honeywell International Inc.

Morristown, New Jersey

Entity:

Large

TITLE

AIRCRAFT CABIN PERSONAL TELEPHONE MICROCELL

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of provisional application no. 60/157,897, filed October 5, 1999.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to mobile telecommunications. More particularly, the present invention relates to a system and method for two-way telecommunications using a wireless telephone on an aircraft, and even more particularly on an aircraft that is maneuvering under its own power, i.e., is taxiing on the runway or is in flight.

15

20

2. Description of the Related Art

Current airline practice is to allow normal personal cellphone use only while the aircraft is at the gate and the doors are open. The use of personal, wireless phones while on-board a maneuvering aircraft is typically prohibited because the radio frequency (RF) emissions from the wireless phone can interfere with the aircraft's systems, for example, communication systems, navigation systems, etc. Additionally, an aircraft in flight provides an on-board cellular terminal user with line of site to many cellphone base stations simultaneously,

10

15

which may overload or interfere with the ground networks if the cellphone simultaneously transmits signals to several base stations.

Conventional air-to-ground telecommunication systems, such as the Claircom AT&T Wireless system and the GTE Airfone system used on board many commercial airliners in the USA and satellite communications systems used on some international airliners, require a passenger to use a telephone installed in the seatback or armrest of the aircraft to initiate a telephone call. The seatback phone connects the aircraft passenger to a ground-based radio station which in turn connects to the public switched telephone network (PSTN). The PSTN is the everyday telephone network (local and long distance) infrastructure operated by telephone carriers, such as AT&T, MCI, Sprint, etc. However, the passengers are still prohibited from using the personal phone to which they are accustomed, depriving them of their normal service subscriptions and also their personal phone's features, such as speed dial and personal phone book. The passenger also pays higher access fees to use the seatback phone installed in the aircraft, and it is very cumbersome, or in some cases impossible, to receive incoming calls on the seatback phones, resulting in passengers being unable to receive calls at all during the flight.

There is a need, therefore, for an improved telecommunication system that
will allow the use of a personal wireless telephone while on board a maneuvering aircraft.

10

15

20

SUMMARY OF THE INVENTION

It is a general object of the present invention to provide a system and method for two-way telecommunications using a personal, wireless telephone on board a maneuvering aircraft.

It is another object of the present invention to provide a system and method for two-way telecommunications on board a maneuvering aircraft that allows a user to initiate and receive calls from a personal, wireless telephone.

In accordance with the objects described above, one aspect of the present invention includes a telecommunication system having an interface device on board an aircraft that interfaces with a wireless phone of a user inside the aircraft and with a wireless bearer system, and a controller that controls the interface device to maintain RF emissions of the wireless phone below a predetermined level. The interface device receives signals from and transmits signals to the wireless phone, receives signals from and transmitting signals to the wireless bearer system, and interfaces through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network. The predetermined level is a level above which RF emissions will interfere with aircraft systems. The telecommunication system may also include one or more of a wireless bearer system gateway on board the aircraft that converts signals received from the wireless phone to protocols of the wireless bearer system and that converts signals received from the wireless bearer system to protocols of the wireless phone, an antenna in a cabin of the aircraft that receives output signals from the wireless phone and conveys the output signals to the interface device, a

15

20

media converter that conveys the signals between the antenna and the interface device, an RF detector that detects unwanted RF emissions above the predetermined level and unsupported cellphone types where the controller alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by the RF detector, and an external antenna that respectively transmits and receives direct cellular signals to and from the wireless phone when the aircraft is on the ground.

In another aspect of the present invention, a telecommunication system includes means on board an aircraft for interfacing with a wireless phone of a user inside the aircraft and with a wireless bearer system, and means for controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level above which RF emissions will interfere with aircraft systems. The means for interfacing is for receiving signals from and transmitting signals to the wireless phone, for receiving signals from and transmitting signals to the wireless bearer system, and for interfacing through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network. The telecommunication system may also include one or more of means on board the aircraft for converting signals received from the wireless phone to protocols of the wireless bearer system and for converting signals received from the wireless bearer system to protocols of the wireless phone, means for detecting unwanted RF emissions above the predetermined level and unsupported cellphone types where the means for controlling alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by the means for detecting,

10

15

20

and means for respectively transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

In yet another aspect of the present invention, a method of two-way communications using a wireless phone on board an aircraft includes the steps of interfacing on board the aircraft with the wireless phone of a user inside the aircraft and with a wireless bearer system, and controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level above which RF emissions will interfere with aircraft systems. The interfacing step includes receiving signals from and transmitting signals to the wireless phone, receiving signals from and transmitting signals to the wireless bearer system, and interfacing through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network. The method may also include one or more of converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone, detecting unwanted RF emissions above the predetermined level and unsupported cellphone types where the controlling step includes alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in the detecting step, and transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

In still another aspect of the present invention, computer executable code for implementing a method of two-way communications using a wireless phone on board an aircraft includes code for executing the steps of interfacing on board the

15

20

aircraft with a wireless phone of a user inside the aircraft and with a wireless bearer system, and controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level above which RF emissions will interfere with aircraft systems. The interfacing step includes receiving signals from and transmitting signals to the wireless phone, receiving signals from and transmitting signals to the wireless bearer system, and interfacing through the wireless bearer system with a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network. The computer executable code may also include code for executing one or more of converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone, detecting unwanted RF emissions above the predetermined level and unsupported cellphone types where the controlling step includes alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in the detecting step, and transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

In another aspect of the present invention, a method of two-way communications using a wireless phone on board an aircraft includes the steps of providing a base station on the aircraft to receive outbound signals from the wireless phone, and transmitting the outbound signals from the aircraft to a wireless bearer system for communication to a ground earth station. The method may also include one or more of receiving, by the base station, inbound signals from the wireless bearer system, transmitting the inbound signals from the base

20

station to the wireless phone, interfacing, through the wireless bearer system, the
base station with a cellular network and then with a public switched telephone
network to register the wireless phone as a roaming subscriber on the contacted
cellular network, controlling RF emissions of the wireless phone to maintain the

RF emissions below a predetermined level above which RF emissions will
interfere with aircraft systems, converting signals received from the wireless phone
to protocols of the wireless bearer system and converting signals received from the
wireless bearer system to protocols of the wireless phone, detecting unwanted RF
emissions above the predetermined level and unsupported cellphone types where
the controlling step includes alerting crew members of the aircraft to the unwanted
RF emissions and unsupported cellphone types detected in the detecting step, and
transmitting and receiving direct cellular signals to and from the wireless phone
when the aircraft is on the ground.

These and other aspects, objects, and features of the present invention will become apparent from the following detailed description of the preferred embodiments, read in conjunction with, and reference to, the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram showing the telecommunication system according to the present invention;

Figure 2 is a block diagram showing an embodiment of the telecommunication system according to the present invention; and

10

15

20

Figure 3 is a block diagram showing a ground earth station that operates with the telecommunication system of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

While the present invention applies to all personal, wireless phone use on-board an aircraft, it is particularly beneficial for use in flight, because it provides a system and method for passengers to use a personal, wireless phone to initiate and receive calls on board a maneuvering aircraft. In doing so, the present invention includes an on-board base station that interfaces between the passenger's personal phone and a Satellite Communications (SATCOM) system, thereby connecting the personal phone to the PSTN. The present invention also controls the output of the personal phone below an acceptable level, thereby preventing interference with the aircraft's systems.

A SATCOM system refers to the method of making a communications transfer by transmitting between a ground or aircraft-based mobile satellite terminal and a satellite vehicle in space. The communications signal is transferred between the satellite and a fixed ground station and between the ground station and the public voice and data networks.

Each of the elements shown in block outline in Figure 1, as well as in Figures 2 and 3, is well known <u>per se</u>, and a specific type of construction is not critical to carrying out the invention or to a disclosure of the best mode for carrying out the invention.

As shown in Figure 1, the system according to the present invention includes a cellular base station (including an interface device, for example, a

microcell or picocell) 104 installed on the aircraft. The base station 104 interfaces the personal, wireless phones 102 of the passengers in the aircraft's cabin with a wireless bearer system 106. The wireless bearer system 106 completes the call to or from the cellular network 108, which connects to the public switched telephone network (PSTN) 110.

In operation, the on-board base station 104, in conjunction with its computer controller (described below), interfaces with the personal phones 102 to control their power level and RF emissions and to transmit and receive signals to and from the personal phones. The on-board base station 104 also interfaces with the PSTN 110 through the wireless bearer system 106 to register the personal phones as normal roaming subscribers and to complete calls to or from the personal phones. A roaming subscriber is someone who is using a cellphone outside their normal home area and within an area serviced by a cellular service provider which is not the one with whom the subscriber has his agreement and to whom he pays charges. The home network operators typically have roaming agreements with other network operators to provide service to customers outside their home area.

The on-board base station of the present invention includes a personal wireless phone base station, for example, a microcell or picocell (described in detail below), modified to operate in the aeronautical environment. The wireless phone base station is a radio transceiver that can communicate using wireless RF radiation with user terminals within its local, limited area, i.e., it transmits RF signals to and receives RF signals from the user terminals. It may also encapsulate additional functions, such as time synchronization with user terminals, signal

10

15

20

decoding and encoding, and transmission rate adaptation between a terminal interface (for example, a wireless phone), and it may also provide a beacon signal for user terminals to be able to link to the base station.

Modifications to the wireless base station are necessary to make the unit rugged enough to operate in the physical environment of an airplane, i.e., so that it will meet the performance requirements in an environment of vibration, altitude, temperature, power fluctuations, etc. Typical modifications to standard commercial electronic systems for installation on an aircraft may include: 1) Additional provisions for shock mounting of components to avoid vibration and gravitational forces dislodging or disconnecting them during aircraft operation; 2) Replacement or substitution of electronic components to provide more reliable operation and less susceptibility to changes in pressure, temperature, or power fluctuations; 3) Provision of additional heating and/or cooling mechanisms (fans, changed airflow, heatsinks, temperature-sensitive air heaters, etc.); 4) Replacement of components and/or provision of tighter case seals, use of different sealing materials, or replacement of cables and connectors in order to a) reduce emitted and conducted radiation which could interfere with, or be susceptible to, radiation from other electronic systems on board the aircraft, b) provide waterproofing where the equipment may be subjected to liquid spills, c) reduce flammability to required airworthiness standards, and d) avoid the production of harmful gases if the equipment is subjected to fire; 5) Replacement of power supply components in order to meet aircraft supply characteristics of either 28V DC or 115V AC at 400 Hertz as provided on board commercial and business aircraft; and (6) Uprating the power supply.

Additionally, the on-board base station is programmed to control the power level of the personal phones so that radiated emissions remain lower than a predetermined level, thereby controlling the probability of interfering with aircraft systems. The predetermined level corresponds to levels of acceptable emissions within aircraft, which are specified in Radio Technical Commission for Aeronautics, Inc. (RTCA) document DO-160D and vary for different aircraft operating conditions, aircraft types, and frequencies within the RF spectrum. The disclosure of RTCA document DO-160D is hereby incorporated by reference. The present invention controls emissions within the requirements in that document and also detects radiated emissions outside the acceptable limits.

An embodiment of the present invention illustrating details of the on-board base station 104 will be described with reference to Figure 2. An indoor antenna, or antennas, 210 in the aircraft's cabin receives signals from and transmits signals to personal phones of the passengers. The antenna is an internal, in-building type antenna, such as a conventional antenna used in a tunnel, cabled directly to a base station, and therefore does not require line-of-sight-detection from the subscriber's terminal to the wireless base station. A media converter 208, such as a coaxial cable, fiber optic cable, or the like, relays the signals between the antenna 210 and an RF repeater 204. A controller 202, including a power supply, controls the RF repeater to receive and send the signals between the antenna 210 and a microcell 214, and it performs a control function that causes the microcell 214 to minimize RF emissions from personal phones in the cabin and to maintain the power output at reasonable levels to avoid interference. The controller 202 is a computer programmed to perform the functions discussed above or to run software designed

to perform those functions. Alternatively, the controller could be a digital or analog circuit that performs those functions. An RF detector 206 detects unwanted RF emissions and unsupported cellphone types and reports to the controller 202, which alerts crew members to their presence.

In this embodiment, signals between the aircraft and the ground are transmitted using a SATCOM system 218 as the wireless bearer system 106 (Figure 1). A SATCOM gateway 216 on board the aircraft interfaces the SATCOM system 218 with the microcell 214. An external antenna 212 also allows direct cellular communications when RF emissions from personal phones are not hazardous to the flight, for example, when the aircraft is on the ground and is not moving under its own power. Direct cellular communications are communications direct from the user handset to a ground base station of a nearby cellular network using wireless transmission without the necessity of using the on-board microcell.

As shown in Figure 3, the relevant satellite ground earth stations for completing calls with the telecommunication system in the aircraft include a satellite 302, that receives signals from and transmits signals to the SATCOM system 218 (Figure 2), and a SATCOM gateway 304 that converts the signals to the correct protocols for communication between the Cellular Network Switching Center 306 and the SATCOM system 218. The signals are then transmitted to the appropriate cellular network(s). The cellular network determines the appropriate routing for the call and is connected to the PSTN, thus allowing a cellular subscriber to make calls to a fixed telephone and vice versa.

In the ground system, the ground earth station communicates with the base station on the airplane via satellite through the SATCOM system. The SATCOM system provides a path for multiple cellular channels to be transmitted and received by the airplane. The SATCOM gateway on the ground emulates a base station to the cellular network and its switching center and converts between SATCOM protocols and the cellular network protocols of the switching center.

The gateway system of the ground earth station appears to one or more connected cellular networks as a standard base station operating as part of the relevant cellular network. It therefore converts the SATCOM protocols into cellular protocols and vice versa. The standard link between a base station and the nearest network switch center is usually implemented with a CEPT E1 or T1 digital link carrying multiplexed voice and data traffic. Voice traffic on the SATCOM bearer system is de-multiplexed, if necessary, and converted from the compressed forms used for SATCOM voice traffic to the protocols used within the cellular networks. The reverse procedure is required for voice traffic originating on the ground cellular network side of the SATCOM gateway.

The present invention meets the need for passengers to keep in touch while traveling. The on-board base station keeps their personal phones connected to the ground network as normal roaming subscribers, and the passengers can send and receive calls just like any other cellular roaming subscriber. Additionally, the passengers can use the personal phone to which they are accustomed, thereby allowing them to have full access to their phone's features, such as speed dial, phone books, voice mail, text messaging, etc. The system allows the use of personal cell phones on board an operating aircraft by controlling their RF outputs

10

15

20

to acceptable levels and by using antennas in the aircraft's cabin to receive signals from and transmit signals to the personal phones.

The present invention is especially useful when operating outside cellular partners' networks, because it uses a SATCOM system to communicate the signals to and from the ground. It is also appropriate for international applications.

A method according to the present invention for providing two-way telecommunications using a personal, wireless phone on board an aircraft includes the steps of providing a base station on the aircraft to receive outbound signals from the wireless phone, and transmitting the outbound signals from the aircraft to a wireless bearer system for communication to a ground earth station. The base station may control RF emissions of the personal phone to maintain the RF emissions below an acceptable level. The method may also include the steps of the base station receiving inbound signals from the wireless bearer system and transmitting the inbound signals to the wireless phone, and converting the output signals to protocols of the wireless bearer system prior to transmitting the output signals to the wireless bearer system and converting the input signals from the wireless bearer system protocols prior to transmitting the input signals to the wireless bearer system protocols prior to transmitting the input signals to the personal phones on the aircraft.

It is preferable to use the present invention with computer hardware that performs the processing functions. As will be appreciated by those skilled in the art, the systems, methods, and procedures described herein can be embodied in a programmable computer, computer executable software, or digital circuitry. The software can be stored on computer readable media, for example, on a floppy disk, RAM, ROM, a hard disk, removable media, flash memory, memory sticks, optical

10

media, magneto-optical media, CD-ROMs, etc. The digital circuitry can include integrated circuits, gate arrays, building block logic, field programmable gate arrays (FPGA), etc.

Although specific embodiments of the present invention have been described above in detail, it will be understood that this description is merely for purposes of illustration. Various modifications of, and equivalent steps corresponding to, the disclosed aspects of the preferred embodiments, in addition to those described above, may be made by those skilled in the art without departing from the spirit of the present invention defined in the following claims, the scope of which is to be accorded the broadest interpretation so as to encompass such modifications and equivalent structures.

I CLAIM:

5

10

15

20

1. A telecommunication system, comprising:

an interface device on board an aircraft that interfaces with a wireless phone of a user inside the aircraft and with a wireless bearer system; and a controller that controls RF emissions of the wireless phone to maintain the RF emissions below a predetermined level.

2. A telecommunication system according to Claim 1, wherein the wireless bearer system is a SATCOM system,

wherein said interface device receives signals from and transmits signals to the wireless phone and receives signals from and transmits signals to the SATCOM system, and

wherein said controller controls said interface device to maintain the RF emissions of the wireless phone below a predetermined level.

- 3. A telecommunication system according to Claim 2, wherein said interface device also interfaces through the SATCOM system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network.
- 4. A telecommunication system according to Claim 1, wherein the predetermined level is a level above which RF emissions will interfere with aircraft systems.
- 5. A telecommunication system according to Claim 2, further comprising:

a SATCOM gateway on board the aircraft that converts signals received

15

20

from the wireless phone to protocols of the SATCOM system and that converts signals received from the SATCOM system to protocols of the wireless phone.

6. A telecommunication system according to Claim 1, further comprising:

an antenna in a cabin of the aircraft that receives output signals from the wireless phone and conveys the output signals to said interface device.

7. A telecommunication system according to Claim 6, further comprising:

a media converter that conveys the signals between said antenna and said interface device.

8. A telecommunication system according to Claim 1, further comprising:

an RF detector that detects unwanted RF emissions above the predetermined level and unsupported cellphone types,

wherein said controller alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by said RF detector.

9. A telecommunication system according to Claim 1, further comprising:

an external antenna that respectively transmits and receives direct cellular signals to and from the wireless phone when the aircraft is on the ground.

10. A telecommunication system according to Claim 1, wherein said interface device is a microcell.

10

15

20

11. A telecommunication system according to Claim 1, wherein said interface device is a picocell.

12. A telecommunication system, comprising:

an interface device on board an aircraft that interfaces with a wireless phone of a user inside the aircraft and with a SATCOM system, said interface device receiving signals from and transmitting signals to the wireless phone, receiving signals from and transmitting signals to the SATCOM system, and interfacing through the SATCOM system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network;

a controller that controls said interface device to maintain RF emissions of the wireless phone below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems;

a SATCOM gateway on board the aircraft that converts signals received from the wireless phone to protocols of the SATCOM system and that converts signals received from the SATCOM system to protocols of the wireless phone;

an antenna in a cabin of the aircraft that receives output signals from the wireless phone and conveys the output signals to said interface device;

a media converter that conveys the signals between said antenna and said interface device;

an RF detector that detects unwanted RF emissions above the predetermined level and unsupported cellphone types, wherein said controller alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by said RF detector; and

an external antenna that respectively transmits and receives direct cellular signals to and from the wireless phone when the aircraft is on the ground.

13. A telecommunication system, comprising;

means on board an aircraft for interfacing with a wireless phone of a user
inside the aircraft and with a wireless bearer system;

means for controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems,

wherein said means for interfacing receives signals from and transmits

signals to the wireless phone and receives signals from and transmits signals to the wireless bearer system.

14. A telecommunication system according to Claim 13, wherein the wireless bearer system is a SATCOM system, and

wherein said means for interfacing also interfaces through the SATCOM system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network

- 15. A telecommunication system according to Claim 14, further comprising:
- means on board the aircraft for converting signals received from the wireless phone to protocols of the SATCOM system and for converting signals received from the SATCOM system to protocols of the wireless phone.

10

15

20

16. A telecommunication system according to Claim 13, further comprising:

means for detecting unwanted RF emissions above the predetermined level and unsupported cellphone types,

wherein said means for controlling alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by said means for detecting.

17. A telecommunication system according to Claim 13, further comprising:

means for respectively transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

18. A telecommunication system, comprising;

means on board an aircraft for interfacing with a wireless phone of a user inside the aircraft and with a wireless bearer system, said means for interfacing for receiving signals from and transmitting signals to the wireless phone, for receiving signals from and transmitting signals to the wireless bearer system, and for interfacing through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network;

means for controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems;

means on board the aircraft for converting signals received from the wireless phone to protocols of the wireless bearer system and for converting

15

20

signals received from the wireless bearer system to protocols of the wireless phone;

means for detecting unwanted RF emissions above the predetermined level and unsupported cellphone types, wherein said means for controlling alerts crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected by said means for detecting; and

means for respectively transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

19. A method of two-way communications using a wireless phone on board an aircraft, said method comprising the steps of:

interfacing on board the aircraft with the wireless phone of a user inside the aircraft and with a wireless bearer system; and

controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level.

20. A method according to Claim 19, wherein the wireless bearer system is a SATCOM system, and

wherein said interfacing step comprises receiving signals from and transmitting signals to the wireless phone and receiving signals from and transmitting signals to the SATCOM system.

21. A method according to Claim 19, wherein said interfacing step further comprises interfacing through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network.

15

20

- 22. A method according to Claim 19, wherein the predetermined level is a level above which RF emissions will interfere with aircraft systems.
- 23. A method according to Claim 20, further comprising the step of:
 converting signals received from the wireless phone to protocols of the
 SATCOM system and converting signals received from the SATCOM system to protocols of the wireless phone.
 - 24. A method according to Claim 19, further comprising the step of:
 detecting unwanted RF emissions above the predetermined level and
 unsupported cellphone types,

wherein said controlling step comprises alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in said detecting step.

- 25. A method according to Claim 19, further comprising the step of: transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.
 - 26. A method of two-way communications using a wireless phone on board an aircraft, said method comprising the steps of:

interfacing on board the aircraft with the wireless phone of a user inside the aircraft and with a wireless bearer system, said interfacing step comprising receiving signals from and transmitting signals to the wireless phone, receiving signals from and transmitting signals to the wireless bearer system, and interfacing through the wireless bearer system to a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber

10

20

on the contacted cellular network;

controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems;

converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone;

detecting unwanted RF emissions above the predetermined level and unsupported cellphone types, wherein said controlling step comprises alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in said detecting step; and

transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

27. Computer executable code for implementing a method of two-way

communications using a wireless phone on board an aircraft, said code for executing the steps comprising:

interfacing on board the aircraft with a wireless phone of a user inside the aircraft and with a wireless bearer system; and

controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level.

28. Computer executable code according to Claim 27, wherein said interfacing step comprises receiving signals from and transmitting signals to the wireless phone and receiving signals from and transmitting signals to the wireless bearer system.

10

20

- 29. Computer executable code according to Claim 28, wherein said interfacing step further comprises interfacing through the wireless bearer system with a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network.
- 30. Computer executable code according to Claim 27, wherein the predetermined level is a level above which RF emissions will interfere with aircraft systems.
- 31. Computer executable code according to Claim 27, wherein the wireless bearer system is a SATCOM system, and

said code for further executing the step of converting signals received from the wireless phone to protocols of the SATCOM system and converting signals received from the SATCOM system to protocols of the wireless phone.

32. Computer executable code according to Claim 27, said code for further executing the step of:

detecting unwanted RF emissions above the predetermined level and unsupported cellphone types,

wherein said controlling step comprises alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in said detecting step.

33. Computer executable code according to Claim 27, said code for further executing the step of:

10

15

20

transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

34. Computer executable code for implementing a method of two-way communications using a wireless phone on board an aircraft, said code for executing the steps comprising:

interfacing on board the aircraft with a wireless phone of a user inside the aircraft and with a wireless bearer system, said interfacing step comprising receiving signals from and transmitting signals to the wireless phone, receiving signals from and transmitting signals to the wireless bearer system, and interfacing through the wireless bearer system with a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network;

controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems;

converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone;

detecting unwanted RF emissions above the predetermined level and unsupported cellphone types, wherein said controlling step comprises alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in said detecting step; and

transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.

10

15

35. A method of two-way communications using a wireless phone on board an aircraft, said method comprising the steps of:

providing a base station on the aircraft to receive outbound signals from the wireless phone; and

transmitting the outbound signals from the aircraft to a wireless bearer system for communication to a ground earth station.

36. A method according to Claim 35, further comprising the steps of: receiving, by the base station, inbound signals from the wireless bearer system; and

transmitting the inbound signals from the base station to the wireless phone.

37. A method according to Claim 36, further comprising the step of: interfacing, through the wireless bearer system, the base station with a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network,

wherein the base station controls RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level above which RF emissions will interfere with aircraft systems.

38. A method according to Claim 36, further comprising the step of:

converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone.

20

39. A method according to Claim 36, further comprising the step of: detecting unwanted RF emissions above the predetermined level and unsupported cellphone types,

wherein the base station alerts crew members of the aircraft to the

unwanted RF emissions and unsupported cellphone types detected in said detecting

step.

- 40. A method according to Claim 36, further comprising the step of: transmitting and receiving direct cellular signals to and from the wireless phone when the aircraft is on the ground.
- 41. A method of two-way communications using a wireless phone on board an aircraft, said method comprising the steps of:

providing a base station on the aircraft to receive outbound signals from the wireless phone;

transmitting the outbound signals from the aircraft to a wireless bearer system for communication to a ground earth station;

receiving, by the base station, inbound signals from the wireless bearer system;

transmitting the inbound signals from the base station to the wireless phone;

interfacing, through the wireless bearer system, the base station with a cellular network and then with a public switched telephone network to register the wireless phone as a roaming subscriber on the contacted cellular network;

controlling RF emissions of the wireless phone to maintain the RF emissions below a predetermined level, the predetermined level being a level

above which RF emissions will interfere with aircraft systems;

converting signals received from the wireless phone to protocols of the wireless bearer system and converting signals received from the wireless bearer system to protocols of the wireless phone;

detecting unwanted RF emissions above the predetermined level and unsupported cellphone types, wherein said controlling step comprises alerting crew members of the aircraft to the unwanted RF emissions and unsupported cellphone types detected in said detecting step; and

transmitting and receiving direct cellular signals to and from the wireless

phone when the aircraft is on the ground.

ABSTRACT OF THE DISCLOSURE

A telecommunication system includes an interface device on board an aircraft that interfaces with a wireless phone of a user inside the aircraft and with a wireless bearer system, and a controller that controls the interface device to maintain RF emissions of the wireless phone below a predetermined level above which RF emissions will interfere with aircraft systems. The system may also include one or more of a wireless bearer system gateway on board the aircraft that converts signals received from the wireless phone to protocols of the wireless bearer system and that converts signals received from the wireless bearer system to protocols of the wireless phone, an antenna in a cabin of the aircraft that receives output signals from the wireless phone and conveys the output signals to the interface device, a media converter that conveys the signals between the antenna and the interface device, an RF detector that detects unwanted RF emissions above the predetermined level and unsupported cellphone types, and an external antenna that respectively transmits and receives direct cellular signals to and from the wireless phone when the aircraft is on the ground.





Figure 1






Figure 3

Attorney's Docket No.: 462-99-012 Page 1 of 2

DECLARATION FOR PATENT APPLICATION SOLE OR JOINT

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention titled:

AIRCRAFT COMMUNICATION FREQUENCY NOMINATION

the specification of which is attached hereto.

I HEREBY STATE THAT I HAVE REVIEWED AND UNDERSTAND THE CONTENTS OF THE ABOVE-IDENTIFIED SPECIFICATION, INCLUDING THE CLAIMS.

I ACKNOWLEDGE THE DUTY TO DISCLOSE INFORMATION WHICH IS MATERIAL TO THE EXAMINATION OF THIS APPLICATION IN ACCORDANCE WITH TITLE 37, CODE OF FEDERAL REGULATIONS, §1.56(a).

rior Foreign Application(s)			
(Number)	(Country) (Day/Mor	nth/Year Filed)	Yes No
(Number)	(Country) (Day/Mor	th/Year Filed)	Yes No
PPLICATION IN THE MANNER PROCKNOWLEDGE THE DUTY TO DISEGULATIONS, \$1.56(a) WHICH OCCR PCT INTERNATIONAL FILING D. 60/157,897	10/05/00	E 35, UNITED STATES CO ED IN TITLE 37, CODE O	ODE, §112, I OF FEDERAL AND THE NATIONA Ong
(Application Serial Number)	(Filing Date)	(SIAIUS: Patented, Po	ending, Abandoned)
(Application Serial Number)	(Filing Date)	(STATUS: Patented, Pe	anding Ahandanad)
OWER OF ATTORNEY: As a name	ed inventor, I hereby appoint the following attorneyordemark Office connected herewith (List name and a	s) and/or agent(s) to prosec	· ,
OWER OF ATTORNEY: As a name	ed inventor, I hereby appoint the following attorney	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT	cute this application ar
OWER OF ATTORNEY: As a name	ed inventor, I hereby appoint the following attorneyond and and the following attorneyond and an ATTORNEY HANDLING CASE WITH PATE	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert	cute this application ar
OWER OF ATTORNEY: As a name ansact all business in the Patent and TrailsT SENIOR PATENT COUNSEL AI	ed inventor, I hereby appoint the following attorneyondemark Office connected herewith (List name and IND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert	cute this application ar ION NUMBERS.) t Desmond
OWER OF ATTORNEY: As a name ansact all business in the Patent and TrailsT SENIOR PATENT COUNSEL AI	ed inventor, I hereby appoint the following attorney ademark Office connected herewith (List name and I ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert 1	cute this application at ION NUMBERS.) t Desmond Name
OWER OF ATTORNEY: As a name ansact all business in the Patent and TrailsT SENIOR PATENT COUNSEL AT Name	ed inventor, I hereby appoint the following attorney ademark Office connected herewith (List name and a ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name 35,063	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert Registra	cute this application and ION NUMBERS.) t Desmond Name 8,430
OWER OF ATTORNEY: As a name ansact all business in the Patent and TrailsT SENIOR PATENT COUNSEL All Name Registration Number	and inventor, I hereby appoint the following attorney and and the following attorney and and a ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name 35,063 Registration Number	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert 3 Registra Eric O	cute this application and ION NUMBERS.) t Desmond Name 8,430 ation Number
OWER OF ATTORNEY: As a name ansact all business in the Patent and Tradistration PATENT COUNSEL Al Name Registration Number John Donofrio	and inventor, I hereby appoint the following attorney addemark Office connected herewith (List name and I ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name 35,063 Registration Number Larry Palguta	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert 3: Registra Eric G	cute this application ar ION NUMBERS.) t Desmond Name 8,430 ation Number G. Halsne
Name Registration Number John Donofrio Name	Add inventor, I hereby appoint the following attorney ademark Office connected herewith (List name and a ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name 35,063 Registration Number Larry Palguta Name	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert 3. Registra Eric C	cute this application and ION NUMBERS.) t Desmond Name 8,430 ation Number G. Halsne Name
OWER OF ATTORNEY: As a name ansact all business in the Patent and Tra LIST SENIOR PATENT COUNSEL AI Name Registration Number John Donofrio Name 32,339	Add inventor, I hereby appoint the following attorney ademark Office connected herewith (List name and I ND ATTORNEY HANDLING CASE WITH PATE Loria Yeadon Name 35,063 Registration Number Larry Palguta Name 29,575	s) and/or agent(s) to prosect egistration number). NT OFFICE REGISTRAT Robert 3. Registra Eric C	icute this application and ION NUMBERS.) t Desmond Name 8,430 ation Number G. Halsne Name 6,753

		suing thereon.	
FULL NAME OF	SOLE OR FIRST INVENTOR	David Gilbert	
INVENTOR'S SI			Date
RESIDENCE _	13220 Barkley Street, Overl	and Park, KS 66209	
CITIZENSHIP	United Kingdom		
POST OFFICE A	ADDRESS Same		
FULL NAME OF	F SECOND JOINT INVENTOR		
INVENTOR'S SI	IGNATURE	di d	Date
RESIDENCE _			
CITIZENSHIP			
POST OFFICE A	ADDRESS		
FULL NAME OI	F THIRD JOINT INVENTOR		Date
RESIDENCE			
CITIZENSHIP			
POST OFFICE A			
FULL NAME O	F FOURTH JOINT INVENTOR		
INVENTOR'S S	SIGNATURE		Date
RESIDENCE			
CITIZENSHIP			
POST OFFICE A	ADDRESS		
FULL NAME O	F FIFTH JOINT INVENTOR		
INIVENITOR'S S	SIGNATURE		Date
INVENTOR 5 5			